

Product Specification

Article Name	ZBA Mesh
Article number	702
Colorno.	60226
Color	Black
Range	Pleated Mesh
Raw Gauze Code	ZBA
Yarn Composition	100 % Polyester

Aspect		Value	Unit	Tolerance	Test-Method
Weight	c.	85	g/m ²	± 10%	ISO 3801
Thickness	c.	0,33	mm	± 0,05 mm	ISO 5084
Stiffness	Length	>17	cm		VHT 2018
Stiffness	Width	>14	cm		VHT 2018
Memory of Pleating		<20	cm		VHT 2013
Tensile Strength	Length	>325	N/5cm		EN 13934-1:2013
Tensile Strength	Width	>300	N/5cm		EN 13934-1:2013
Elongation	Length	>15	%		EN 13934-1:2013
Elongation	Width	>25	%		EN 13934-1:2013
Light Fastness		6-7			ISO EN 105 B04
Light Fastness	FAKRA	4			ISO EN 105 B06
Openness Factor		62	%		n.a.
Flame Retardent		No			n.a.
Water Repellency		No			n.a.
Tolerance Pleat		± 0,5	mm		
Width		± 1,0	%		

Aspects weight, thickness, stiffness, tensile strength and elongation are measured from unpleated material.
10 faults per 100mtr are accepted. A fault must be smaller than 20cms of length.

Date of Issue	22-6-2020
Revision Date	30-11-2018

Our products comply with the requirements of the REACH Regulation (EC regulation 1907/2006)

L. van Heek Textiles B.V.
Postbus 1, NL-7580 AA Losser
Gronausestraat 309, NL-7581 CV Losser
Chamber of Commerce: 06073308

T+31 (0)53 535371111
F+31 (0)53 535371140
www.vanheektextiles.com
info@vanheektextiles.com