

Product Specification

Article Name	ZAA Pleated Mesh
Article number	706
Colorno.	60241
Color	Black
Range	Pleated Mesh
Raw Gauze Code	ZAA
Yarn Composition	100 % Polyester

Aspect		Value	Unit	Test-Method
Weight	c.	63	g/m ²	ISO 3801
Thickness	c.	0,27	mm	ISO 5084
Stiffness	Length	>10	cm	VHT 2010
Stiffness	Width	>10	cm	VHT 2010
Memory of Pleating		<15	cm	VHT 2013
Tensile Strength	Length	>125	N/5cm	EN 13934-1:2013
Tensile Strength	Width	>200	N/5cm	EN 13934-1:2013
Elongation	Length	>10	%	EN 13934-1:2013
Elongation	Width	>30	%	EN 13934-1:2013
Light Fastness		6-7		ISO EN 105 B04
Light Fastness	FAKRA	4		ISO EN 105 B06
Openness Factor		75	%	n.a.
Flame Retardant		No		n.a.
Water Repellency		No		n.a.
Tolerance Pleat		± 0,5	mm	
Width		± 1,0	%	

Aspects weight, thickness, stiffness, tensile strength and elongation are measured from unpleated material.
10 faults per 100mtr are accepted. A fault must be smaller than 20cms of length.

Date of Issue	22/02/2021
Revision Date	07/07/2017

Our products comply with the requirements of the REACH Regulation (EC regulation 1907/2006)

L. van Heek Textiles B.V.
Postbus 1, NL-7580 AA Losser
Gronausestraat 309, NL-7581 CV Losser
Chamber of Commerce: 06073308

T+31 (0)53 535371111
F+31 (0)53 535371140
www.vanheektextiles.com
info@vanheektextiles.com