

Product Specification

Article Name	Poll-TEX
Article number	764
Colorno.	60185
Color	Black
Range	Mesh
Raw Gauze Code	ZAL
Yarn Composition	100 % Polyester

Aspect		Value	Unit	Test-Method
Weight	c.	100	g/m ²	ISO 3801
Thickness	c.	0,29	mm	ISO 5084
Stiffness	Length	>7	cm	VHT 2018
Stiffness	Width	>12	cm	VHT 2018
Memory of Pleating		n.a.	cm	n.a.
Tensile Strength	Length	c. 150	N/5cm	EN 13934-1:2013
Tensile Strength	Width	c. 450	N/5cm	EN 13934-1:2013
Elongation	Length	c. 25	%	EN 13934-1:2013
Elongation	Width	c. 15	%	EN 13934-1:2013
Light Fastness		6-7		ISO EN 105 B04
Light Fastness	FAKRA	4		ISO EN 105 B06
Openness Factor		35	%	n.a.
Dimension of opening	L x W	0,2 x 1,2	mm	n.a.
Flame Retardant		No		n.a.
Water Repellency		Reasonable		According VHT 2015
Tolerance Pleat		n.a.	mm	
Width		± 1,0	%	

A roll of 50mtrs may contain a maximum of 3 faults*. The faults must be smaller than 20cms of length.

One of the faults may contain a seam. 1 seam per 50mtrs is accepted.

All faults will be marked at one end of the roll.

* In 50% of the rolls of a shipment an extra fault is allowed.

Date of Issue	16-4-2021
Revision Date	17-5-2018

Our products comply with the requirements of the REACH Regulation (EC regulation 1907/2006)