

PRINTING DATASHEET

	FSC®	weight ≈ gsm	thickness ≈ mm	OFFSET	SCREEN	FOIL	SOLVENT	TONER	UV	LATEX
BRILLIANTA®	FSC®	162	0.33	•	●	●	•	●	●	●
BRILLIANTA CALANDRÉ	FSC®	162	0.31	•	●	●	•	●	●	●
BUCKRAM LIGHT	FSC®	183	0.22	●	●	●	●	●	●	●
BUCKRAM PREMIUM	-	232	0.32	●	●	●	●	●	●	●
DUBLETTA	FSC®	165	0.27	•	●	●	•	•	●	●
ECOJEANS		162	0.40	•	●	●	•	●	●	●
FANCY LINEN	FSC®	160	0.29	●	●	●	●	●	●	●
FANCY METALLIC	FSC®	185	0.32	●	●	●	●	●	●	●
FINESSE	FSC®	175	0.32	●	●	●	•	●	●	●
HALFLINNEN DARK	FSC®	258	0.50	•	•	•	•	•	•	•
HALFLINNEN LIGHT	-	172	0.34	•	●	●	•	•	•	•
IMPRIMEX	-	200	0.23	●	●	●	●	●	●	●
MAGIC	FSC®	180	0.33	●	●	●	●	●	●	●
MAGIC CHIC	FSC®	180	0.31	●	●	●	●	●	●	●
METALLIUM	-	240	0.32	●	●	●	●	●	●	●
NATUURLINNEN	FSC®	175	0.41	•	●	●	•	●	●	●
PRINTEX	FSC®	190	0.30	●	●	●	●	●	●	●
REPROTEX	-	320	0.40	●	●	●	●	●	●	●
SAPHIR	FSC®	142	0.27	•	●	●	•	●	●	●
SATINETTE	-	200	0.34	●	●	●	•	●	●	●
SENATOR	-	222	0.35	•	●	●	•	●	●	●
BRILLIANCE	FSC®	156	0.32	•	●	●	•	●	●	●
REGENT	-	162	0.27	●	●	●	•	●	●	●
REGINA	-	180	0.33	•	•	•	•	•	•	•

PHASING
OUT

We recommend to evaluate the printing results with your own equipment to make sure the outcome meets your expectations.