



van Heek textiles

Product specification

Name	Pleated mesh all colours with lotus effect 80 g/m²		
Raw gauze code	ZBA		
Yarn type length	100 % polyester		
Yarn type width	100 % polyester		
Weight	80	g/m²	± 10%
Thickness	0,38	mm	± 0,05 mm
Stiffness length	>15	cm	Shirley stiffness test
Stiffness width	> 15	cm	Shirley stiffness test
Memory of pleating	< 20	cm	according test VHT 2013
Tear strength length	330	N/5cm	
Tear strength width	325	N/5cm	
Elongation length	34	%	
Elongation width	45	%	
Light fastness	3-4	according ISO EN 105 B04	
Light fastness	2	according FAKRA ISO EN 105 B06	
Sun protection	38	% blockage	
Openness	62	%	
Flame retardent	no	n.a.	
Water repellency	yes	according VHT 2015	
Tolerance pleat	± 0,5	mm	
Tolerance width	± 1,0	cm	
Date of issue	1-12-2016		
Revision date			

Our products comply with the requirements of the REACH Regulation (EC regulation 1907/2006)

Subsidiary of:
Van Heek-Scholco International bv
Postbus 1, NL-7580 AA Losser
Gronausestraat 309, NL-7581 CV Losser
Chamber of Commerce: 06073308

T+31 (0)53 535371111
F+31 (0)53 535371140
www.vanheektextiles.com
info@vanheektextiles.com