



van Heek textiles

## Product specification

Name	<b>Pleated mesh flame retardent and with lotus effect 80 g/m2</b>		
Raw gauze code	ZBA		
Yarn type length	100 % polyester		
Yarn type width	100 % polyester		
Weight	80	<b>g/m<sup>2</sup></b>	± 10%
Thickness	0,38	<b>mm</b>	± 0,05 mm
Stiffness length	>15	<b>cm</b>	<b>Shirley stiffness test</b>
Stiffness width	> 15	<b>cm</b>	<b>Shirley stiffness test</b>
Memory of pleating	< 20	<b>cm</b>	<b>according test VHT 2013</b>
Tear strength length	330	<b>N/5cm</b>	
Tear strength width	325	<b>N/5cm</b>	
Elongation length	34	<b>%</b>	
Elongation width	45	<b>%</b>	
Light fastness	6-7	<b>according ISO EN 105 B04</b>	
Light fastness	4	<b>according FAKRA ISO EN 105 B06</b>	
Sun protection	38	<b>% blockage</b>	
Openness	62	<b>%</b>	
Flame retardent	yes	<b>n.a.</b>	
Water repellency	yes	<b>according VHT 2015</b>	
Tolerance pleat	± 0,5	<b>mm</b>	
Tolerance width	± 1,0	<b>cm</b>	
Date of issue	25-10-2016		
Revision date			

***Our products comply with the requirements of the REACH Regulation (EC regulation 1907/2006)***

Subsidiary of:  
Van Heek-Scholco International bv  
Postbus 1, NL-7580 AA Losser  
Gronausestraat 309, NL-7581 CV Losser  
Chamber of Commerce: 06073308

T+31 (0)53 535371111  
F+31 (0)53 535371140  
[www.vanheektextiles.com](http://www.vanheektextiles.com)  
[info@vanheektextiles.com](mailto:info@vanheektextiles.com)